# **Product data sheet**

Specifications



# Rack PDU, Switched, 1U, 20A, 120V, (8)5-20



AP7901B

U	٧	е	r	٧	ı	e	٧	۷	
---	---	---	---	---	---	---	---	---	--

Usually in Stock

Main	
Main Input Voltage	100 V 120 V
PDU Type	Switched
Main Output Voltage	120 V
Input Connection Type	NEMA L5-20P
Number of rack unit	1U
Cable length	12 ft (3.66 m)
Number of cables	1
Provided Equipment	Cord retention bracket(s) Horizontal mounting brackets User Manual Installation guide

### **Physical**

Color	Black
Height	1.73 in (4.4 cm)
Width	17.52 in (44.5 cm)
Depth	4.25 in (10.8 cm)
Net Weight	5.00 lb(US) (2.27 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Mounting Mode	Rack-mounted
Mounting position	Horizontal

#### Input

Line Rated Current	16 A
Permissible voltage	100120 V
Input current limits	20 A

Load Capacity	1900 VA
Input Frequency	50/60 Hz

#### **Output**

Number of power socket outlets 8 NEMA 5-20R

#### Conformance

Product Certifications	cUL Listed CSA Industry Canada UL Listed
Standards	FCC Part 15 class A ICES-003 UI 60950

#### **Environmental**

Ambient air temperature for operation	32113 °F (045 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (0.0015240.00 m)

# Ordering and shipping details

**GTIN** 731304331575

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.76 in (7 cm)
Package 1 Width	13.50 in (34.3 cm)
Package 1 Length	18.50 in (47 cm)
Package 1 Weight	7.61 lb(US) (3.45 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

### **Contractual warranty**

Warranty

2 years repair or replace

Recommended replacement(s)