



SM80NU-N

HighSecLabs 8-Port KM Switch

| C-KVM



SM80NU-N is an 8-port KM switch. It enables users to share peripherals – keyboard, mouse, audio and USB – between four different networks/computers. It also enables assigning a USB port to a specific computer while switching other peripherals, such as when a USB smart card reader must remain mapped to a certain computer

FEATURES

Smooth Switching Between Computers (Virtual Display Technology) - Automatically switch all peripheral control from one computer to another by dragging the cursor between each computer's display border

Multiple Display Layouts - Associate the cursor with each computer based on how its display is aligned (vertically or horizontally)

Copy & Paste - Transfer text and files between all the computers that are connected to the KVM through the KVM (no network connection is needed between parties). Use standard copy and paste keyboard key combinations (CTRL+C / CTRL+V) or mouse context-menu commands to transfer data between computers that are connected to the KVM

Super Speed USB 3.0 Ports - Transfer data and files between peripherals and computers in USB 3.0 Super Speed rates through the KVM USB 3.0 ports

Express USB Charging - Rapidly charge USB devices connected to the KVM highpower USB port



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|-----------------------|---|
| Console Ports | 2 USB-A connectors for keyboard and mouse;3 USB-A 3.0 connectors for USB devices;1 3.5mm mini jack for unbalanced stereo audio;1 RJ45 connector for control (RDC) |
| Computer Ports | 8 USB-B connectors for keyboard and mouse;8 USB-B 3.0 connectors for USB devices;8 3.5mm mini jacks for unbalanced stereo audio |
| Power Consumption | 35W Max |
| AC Input | 100V to 240V AC |
| Power Type | Internal |
| Operating Temperature | 0° to +40°C (32° to 104°F) |
| Storage Temperature | -20° to +60°C (-4° to 140°F) |
| Humidity | 0% to 80%, RH non-condensing |
| Supported OS | Windows, Linux, Mac |
| Product Certification | CE, RCM, FCC class B, VCCI, TUV US, TUV Canada |
| Product Life-cycle | 10 years |
| Product Dimensions | 44.00cm x 19.20cm x 4.80cm (17.32" x 7.56" x 1.89") W, D, H |
| Product Weight | 2.4kg (5.3lbs) approx |
| Shipping Dimensions | 52.50cm x 27.50cm x 11.00cm (20.67" x 10.83" x 4.33") W, D, H |
| Shipping Weight | 3.1kg (6.8lbs) approx |