




# kramer

## DK42HU-N

HighSecLabs Dual Head 4-Port 4K30 UHD  
HDMI KVM Switch with sUSB

| HDMI | C-KVM



DK42HU-N is a dual head 4-port, 4K30 UHD HDMI KVM switch. It enables users to share peripherals – keyboard, video, mouse, audio, and USB – between four networks/computers. It also enables assigning a USB port to a specific computer while switching other peripherals, such as when a USB smart card reader must remain mapped to a certain computer

## FEATURES

**4K30 UHD Resolution** - Supports resolutions up to 3840×2160

**Extended/Duplicated Display Support** - Enables switching keyboard, mouse and up to 2 displays (either extended or duplicated) between computers

**Multi Display Support** - Change to KM mode to enable switching keyboard and mouse control between computers, when each computer is connected to up to 4 displays (either extended or duplicated)

**Freeze USB** - Assign the USB port to a specific computer while switching the keyboard, video, mouse and audio peripherals between other computers. Useful when a USB device such as a disk-on-key must remain mapped to a certain computer, while the user is working on another computer

**Freeze Audio** - Assign the audio port to a specific computer while switching the keyboard, video, mouse and USB peripherals between other computers. Useful for scenarios where a user has to listen to audio originating from one computer while working on another computer

**Super Speed USB 3.0 Port** - Transfer data and files between peripherals and computers USB 3.0 Super Speed rates through the KVM switch USB 3.0 ports

**Express USB Charging** - Rapidly charge USB devices connected to the high-power USB ports



# kramer

## TECHNICAL SPECIFICATIONS

---

Console Ports	2 HDMI connectors;2 USB-A connectors for keyboard and mouse;4 USB-A 3.0 connectors for USB devices;1 3.5mm mini jack for unbalanced stereo audio;1 3.5mm mini jack for microphone;1 RJ-11 connector for control (RDC)
Computer Ports	8 HDMI connectors;4 USB-B connectors for keyboard and mouse;4 USB-B 3.0 connectors for USB devices;4 3.5mm mini jacks for unbalanced stereo audio;4 3.5mm mini jacks for microphone
Max Resolution	4K30 UHD (3840X2160)
Power Consumption	12V DC, 1.5A
AC Input	100 to 240V AC
Power Type	External
Operating Temperature	32° to 104°F (0° to 40°C)
Storage Temperature	-4° to 140°F (-20° to 60°C)
Humidity	0-80% RH, non-condensing
Supported OS	Windows, Linux, Mac
Product Certification	CE, RCM, FCC class B, VCCI, TUV US, TUV Canada
Product Life-cycle	10 years
Product Dimensions	34.20cm x 15.80cm x 5.70cm (13.46" x 6.22" x 2.24" ) W, D, H
Product Weight	2.0kg (4.3lbs) approx
Shipping Dimensions	42.00cm x 25.00cm x 8.50cm (16.54" x 9.84" x 3.35" ) W, D, H
Shipping Weight	2.6kg (5.6lbs) approx

