CRPN-62B

5,500 lumens, Panorama, single-chip DLP projector



- Razor-sharp images with vibrant colors
- Panoramic canvas
- Compact design
- 24/7 reliability

*Only available at selected distributors

The CRPN-62B is the perfect solution for wide-screen projection in high-end meeting rooms, boardrooms and collaboration rooms that require multi-windowing features.

Better collaboration

Having an efficient and detailed view of complex data sets is paramount in order to make the right decisions. Thanks to the CRPN-62B's unique Panorama (2,560 x 1,080) resolution and 21:9 aspect ratio, you can easily share highly detailed information in a side-by-side manner. Did you know that showing more data on screen simultaneously has a documented effect on work efficiency?* Allowing multiple participants to be on-screen simultaneously and share various types of content, the CRPN-62B enables better collaboration.

High-quality images

With its 5,500 lumens brightness level, the CRPN-62B provides stable, uniform and high-contrast images, that enable you to concentrate better and focus on what matters most in meetings: the agenda. And thanks to its low noise level, working in an environment with front projection has never been less distracting.

Built to last

The CRPN-62B features a filter-free design and reliable DLP® technology for unmatched picture accuracy and low total cost of ownership. Designed for unlimited use, it also comes with a three-year warranty, for true peace of mind.



| Product specifications | CRPN-62B |
|---------------------------------|---|
| General specifications | |
| Projector type | Single-chip DLP projector |
| Technology | LVDC DMD™ with DarkChip3™ |
| Resolution | 2,560 x 1,080 (Panorama) |
| Brightness | 5,500 ANSI lumens |
| Contrast ratio | 6,500:1 |
| Brightness uniformity | >90% |
| Aspect ratio | 21:9 |
| Lens type | All pure glass lenses |
| Lenses | wide angle lens EN42 (0.8:1), ultra wide zoom lens EN46 (0.8-1.21:1), wide angle lens EN43 (1.2-1.7:1), standard zoom EN41 (1.7-2.5:1), long throw zoom EN44 (2.50-4.60 :1), ultra wide fixed EN47 (0.65 : 1) |
| Optical lens shift | Vertical: -222% to +222%; horizontal: -78% to +78% (on zoom lenses) |
| Color correction | RealColor™ |
| Lamps | 2 x 300W UHP Vidi |
| Lamp lifetime | Up to 2,000 hours (full power) / Up to 2,500 hours (eco mode) |
| Lamp house, quick replace | yes |
| Lamp warranty | 500 hours or 90 days |
| Sealed DLP™ core | Yes |
| Orientation | table -ceiling |
| Inputs | 2 x DVI-I; 2 x HDMI 1.3a; 2 x VGA; Video inputs; 1 x component; 1 x S-video |
| Input resolutions | Up to 2,560 x 1,600 pixels input on all models. Output resolution depends on native resolution; HDTV (1080p, 1080i, 720p); EDTV (576p, 480p); SDTV (576i, 480i); NTSC, PAL, SECAM; progressive scan |
| Software tools | Projector Toolset, ProNet |
| Control | $1\mathrm{x}$ RJ-45 TCP/IP; $1\mathrm{x}$ 9-pin D-SUB RS232; $2\mathrm{x}$ $12\mathrm{V}$ programmable trigger (3.5mm mini jack); $1\mathrm{x}$ Wired Remote 3.5mm mini jack; $2\mathrm{x}$ USB |
| Network connection | 10/100 base-T, RJ-45 connection |
| Power requirements | 100-240V / 50-60Hz |
| Power consumption | 912W |
| Noise Level | 34 dB |
| Operational ambient temperature | 10-40°C / 50°-104°F |
| Operational humidity | 20-80% RH |
| Dissipation BTU | max 3,109 BTU/h |
| Dimensions (WxLxH) | 510 x 376 x 233 mm / 20.08 x 14.80 x 9.17 inches |
| Weight | 12.7 kg (28.0 lbs) |
| Standard accessories | Power cord, wireless remote control |
| Certifications | Compliant with FCC, part 15 Class A and CCC, cCSAus, cUL, UL and CE |
| Warranty | Limited 3 years parts and labor. Extendable up to 5. |

Last updated: 09 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.

