

## SPECIFICATION SHEET



## USB-C To HDMI Audio/Video Adapter

- No driver is required which allows for quick setup and no down time.
- Compact light weight design makes it easy to carry for presentations.
- Supports high bandwidth features such as:
  - 4k
  - 3D
- Supports HDCP 2.0
- Reversible, symmetrical USB-C connector.
- 3 Year Warranty.

## Specifications: USB-C To HDMI Audio/Video Adapter

### Electrical Specifications:

---

Voltage Rating	30V
Insulation Resistance	10M $\Omega$ /km
Conductor Resistance	@ 20°C Max

### Physical Specifications:

---

Operating Temperature	0°C to 50°C
Storage Temperature	-25°C to 70°C
Jacket	PVC
Shield	AL-Mylar 100% Coverage
	Braid 16/7/0.12
Drain	32AWG (7/0.08BC)
OD	5.2mm $\pm$ 0.2mm

### Conductor 1: (2 Conductors, 5 Pair)

---

Conductor	32AWG (7/0.08TC)
Insulation	FM-PE, ID:0.62 $\pm$ 0.02mm
Color	White/Brown, White/Red, White/Black, White/Green
Drain	32AWG (7/0.08TC)
Shield	AL-Mylar 100% Coverage

### Conductor 2: (4 Conductors)

---

Conductor	32AWG (7/0.08TC)
Insulation	HD-PE, ID:0.5 $\pm$ 0.03mm
Color	Purple/Yellow/White/Green

### Conductor 3: (1 Conductors)

---

Conductor	28AWG (7/0.12TC)
Insulation	HD-PE, ID:0.7 $\pm$ 0.03mm
Color	Red

