



## TP-873xr

4K HDR HDMI PoC Transmitter with RS-232  
& IR over Long-Reach DGKat 2.0

| HDMI | DGKat | 4K/60 UHD (4:4:4)



TP-873xr is a high-performance, long-reach DGKat™ 2.0 transmitter for 4K@60Hz (4:4:4) HDR HDMI HDCP 2.2 signals, RS-232 and IR signals and 2-way powering over twisted pair. It converts the HDMI, RS-232 and IR input signals into a DGKat™ 2.0 signal and transmits it to the receiver. TP-873xr extends video signals to up to 50m (160ft) at 4K@60Hz (4:4:4) resolution and up to 70m (230ft) at 4K@30Hz (4:4:4) 24bpp resolution over Kramer shielded cables

## FEATURES

**High Performance Extender** - Professional DGKat™ 2.0 transmitter for providing long-reach signals and 2-way power over twisted pair copper infrastructures. PT-873xr employs low-level video compression technology that delivers visually lossless performance for 4K@60Hz (4:4:4) HDR signals with near-zero latency

**HDMI Signal Extension** - HDR, HDCP 2.2 compliant. Supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0

**EDID Pass-through** - Pass-through algorithm ensures Plug and Play operation for HDMI source and display systems

**Multi-channel Audio Extension** - Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound

**Bidirectional RS-232 Extension** - Serial interface data flows in both directions, allowing data transmission and device control

**Bidirectional Infrared Extension** - IR interface data flows in both directions, allowing remote control of peripheral devices located at either end of the extended line

**Cost-effective Maintenance** - Status LED indicators for HDMI and DGKat™ 2.0 ports facilitate easy local and remote maintenance and troubleshooting

**Easy Installation** - Single twisted-pair cable for signal and power wiring. Compact DigiTOOLS® fan-less enclosure for device-back mounting, or side-by-side mounting of 3 units in a 1U rack space with the optional, compatible Kramer rack adapter



# KRAMER

## TECHNICAL SPECIFICATIONS

---

Inputs	1 HDMI On a female HDMI connector
Outputs	1 DGKAt 2.0 On an RJ-45 female connector
Ports	1 RS-232 On a 3-pin terminal block connector 1 IR On a 3.5mm mini jack connector
Video	Transmitted Data Bandwidth: Up to 18Gbps (6Gbps per graphic channel) Max Resolution at High Compression Level 3840x2160@60Hz (4:4:4) 24bpp Max Resolution at Standard Compression Level 4096x2160@60Hz (4:4:4) 24bpp Standards Compliance: HDR10, HDCP 2.2 HDMI Support Deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0
High Compression Reach Extension	Using Shielded UNIKAT Cables Up to 50m (160ft) at 4K@60Hz (4:4:4), Up to 70m (230ft) at 4K@30Hz (4:4:4) or full HD (1080p @60Hz 36bpp) Using Plenum HDKat Cables Up to 40m (130ft) at 4K@60Hz (4:4:4), Up to 50m (160ft) at 4K@60Hz (4:2:0) or full HD (1080p @60Hz 36bpp)
Standard Compression Reach Extension	Using Shielded UNIKAT Cables Up to 35m (110ft) at 4K@60Hz (4:4:4), Up to 70m (230ft) at 4K@30Hz (4:4:4) or full HD (1080p @60Hz 36bpp)
Extension Line	Signal Compression: Standard or high compression level applied to >1080p signals Compliance: DGKAt 2.0
User Interface	Indicators: IN, OUT, and ON LEDs Controls Dip-switches to define compression level
Power	Source: 12V DC, 2A Consumption: (connected to power and providing power to a receiver) 0.87A
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing
Enclosure	Size DigiTOOLS Type Aluminum Cooling Convection ventilation
Accessories	Included 1 power adapter with cord, 1 bracket set
REGULATORY	Safety CE, UL Environmental RoHs, WEEE
Product Dimensions	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
Product Weight	0.2kg (0.5lbs) approx
Shipping Dimensions	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43" ) W, D, H
Shipping Weight	0.7kg (1.5lbs) approx

