



# kramer

## DTAxr-OUT4-F32

4-Channel 4K60 4:2:0 HDMI over Extended Reach HDBaseT Output Card with Selectable Embedded or De-embedded Analog Audio

| Ethernet - RJ-45 | HDCP Compliant  
| Kramer Core | HDBaseT



DTAxr-OUT4-F32 is a four-channel HDMI, analog audio, bidirectional RS-232, Ethernet, & IR over HDBaseT twisted pair transmitter card for the VS-3232 Series Modular Multi-Format Digital Matrix Switchers. The DTAxr-OUT4-F32 outputs four extended reach HDBaseT signals with analog audio, bidirectional RS-232, IR, and Ethernet from the chassis to the line

## FEATURES

**Max. Data Rate** - 10.2Gbps (3.4Gbps per graphics channel)

**Max. Resolution** - 4K@60Hz (4:2:0)

**Analog Audio Embedding/De-embedding** - On the same jack

**HDBaseT Technology** - HDTV compatible, HDCP compliant

**System Range** - Up to 100m at normal mode (4K), up to 130m (430ft) at normal mode (2K), up to 180m (590ft) ultra mode (1080p @60Hz @24bpp). Note: When using Kramer HDBaseT cables

**Ethernet Extension** - Ethernet interface data flows in both directions, allowing extension of up to 100Mbps Ethernet connectivity for LAN communication and device control

**Bidirectional RS-232 Extension** - Serial interface data flows in both directions, allowing data transmission and device control

**Bidirectional Infrared Extension** - IR interface data flows in both directions, allowing remote control of peripheral devices located at either end of the extended line

**3D Pass-Through**



# kramer

## TECHNICAL SPECIFICATIONS

---

Outputs:	4 HDBaseT TP on RJ-45 connectors 4 Balanced audio on terminal block connectors
Ports:	4 RS-232 and 4 IR on 10 pin terminal blocks for bidirectional RS-232 and IR extension; 1 Ethernet on an RJ-45 connector for bidirectional Ethernet extension
BANDWIDTH PER CHANNEL:	Video: 3.4Gbps; Serial Data: 115200
TOTAL BANDWIDTH:	Video: 10.2Gbps; Serial Data: 115200
MAXIMUM RANGE:	Up to 100m at normal mode (4K), up to 130m (430ft) at normal mode (2K), up to 180m (590ft) ultra mode (1080p @60Hz @24bpp).; Note: When using Kramer HDBaseT cables
3D PASS THROUGH:	Supported
Extended Ethernet	Up to 100Mbps extended line rate bandwidth
Extended RS-232	300 to 115200 baud rate
POWER CONSUMPTION:	26W
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
STANDARD COMPLIANCE:	HDCP 1.4, HDMI 1.3a, HDBaseT
SAFETY REGULATORY COMPLIANCE:	CE
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
Product Dimensions	22.00cm x 18.80cm x 2.00cm (8.66" x 7.40" x 0.79" ) W, D, H
Product Weight	0.2kg (0.5lbs) approx
Shipping Dimensions	25.00cm x 22.50cm x 5.50cm (9.84" x 8.86" x 2.17" ) W, D, H
Shipping Weight	0.4kg (0.9lbs) approx