

FI11H-M

HighSecLabs Secure 1-Port HDMI KVM Isolator | HDMI | C-KVM



FI11H-M is a single-port secure isolator for HDMI video and USB. The unit prevents direct contact between the connected computer and its shared peripherals. Maximum security is achieved by keeping the video path separate from the keyboard and mouse even when the unit is powered off

FEATURES

Advanced Isolation Between Computers & Shared Peripherals Unidirectional Data Flow: USB & Video Power Domain Isolation Secure Administrator Access & Log Functions Always-on, Active Anti-tamper System



TECHNICAL SPECIFICATIONS

ENCLOSURE:	Extruded aluminum metal enclosure
POWER REQUIREMENTS:	12V DC, 1A maximum
POWER SUPPLY:	90-240V AC
CONSOLE KEYBOARD INPUT:	USB type-A female connector
CONSOLE MOUSE INPUT:	USB type-A female connector
RESOLUTION SUPPORT:	Up to 2K, 4K UHD (3840 X 2160 pixels) resolutions
CONSOLE DISPLAY PORT:	HDMI female connector
COMPUTER KEYBOARD/MOUSE PORT:	USB Type B
WARRANTY:	3 years
WARRANTY: COMPUTER VIDEO INPUT PLUG:	3 years 1 x HDMI video port
COMPUTER VIDEO	
COMPUTER VIDEO INPUT PLUG:	1 x HDMI video port
COMPUTER VIDEO INPUT PLUG: OPERATING TEMP:	1 x HDMI video port 32° to 104° F (0° to 40° C)
COMPUTER VIDEO INPUT PLUG: OPERATING TEMP: STORAGE TEMP:	1 x HDMI video port 32° to 104° F (0° to 40° C) -20° to 60°C (-4° to 140°F)
COMPUTER VIDEO INPUT PLUG: OPERATING TEMP: STORAGE TEMP: HUMIDITY: PRODUCT DESIGN	1 x HDMI video port 32° to 104° F (0° to 40° C) -20° to 60°C (-4° to 140°F) 0-80% RH, non-condensing
COMPUTER VIDEO INPUT PLUG: OPERATING TEMP: STORAGE TEMP: HUMIDITY: PRODUCT DESIGN LIFE-CYCLE:	1 x HDMI video port 32° to 104° F (0° to 40° C) -20° to 60°C (-4° to 140°F) 0-80% RH, non-condensing 10 years
COMPUTER VIDEO INPUT PLUG: OPERATING TEMP: STORAGE TEMP: HUMIDITY: PRODUCT DESIGN LIFE-CYCLE: Product Dimensions Product Weight	1 x HDMI video port 32° to 104° F (0° to 40° C) -20° to 60°C (-4° to 140°F) 0-80% RH, non-condensing 10 years 14.50cm x 10.50cm x 2.80cm (5.71" x 4.13" x 1.10") W, D, H