

ClickShare C-10

Interactive wireless presentation for any meeting space



- **Interactive features: touchback, annotation and blackboarding**
- **Increased collaboration with 2 sources on screen**
- **Iconic ClickShare Button for employees and guests**
- **100% secure, encrypted and cloud-managed**

ClickShare C-10 brings interactive wireless presentation to any meeting space. Content sharing is simple, with just one click on the ClickShare Button (Windows or Mac) or the ClickShare App (laptop, mobile or tablet). Start presenting within seconds: no cables, no software to download, no training needed.

Product specifications**CLICKSHARE C-10**

| ClickShare Base Unit dimensions | |
|----------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions (HxWxD) | 34 mm x 135 mm x 135 mm |
| Power supply | Standard 110/220 V AC plug or USB-C (only Gen2) |
| Power consumption | Operational: 5-10W, 24W Max |
| Weight | 900 gr |
| General specifications | |
| Operating system | Windows 10 and higher macOS 11 (BigSur) and higher Android v9 and higher (ClickShare App)* iOS 12 and higher (ClickShare App)* |
| Video outputs | 4K UHD (3840*2160) @ 30Hz. HDMI 1.4b or USB-C DisplayPort 1.2 (only Gen2) |
| Audio output | HDMI |
| USB | 1 X USB-A, 1 X USB-C |
| ClickShare Buttons | 1 |
| ClickShare App | Desktop & Mobile |
| Native protocols | Airplay, Google Cast, Miracast* |
| Maximum number of simultaneous connections (with Buttons and/or App) | 32 |
| Noise Level | Max. 25dBA @ 0-30°C Max. 30dBA @ 30-40°C |
| Authentication protocol | WPA2-PSK in stand alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode |
| Wireless transmission protocol | IEEE 802.11 a/g/n/ac and IEEE 802.15.1 |
| Reach | Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz |
| Frequency band | 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) |
| Connections | 1x Ethernet LAN 1Gbit 1x USB-C 2.0 (front); 1x USB-A 2.0 (front) -only Gen2: 1x USB-C 3.0 (front); 1x USB-A 3.0 (front) |
| Temperature range | Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) |
| Humidity | Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing |
| Anti-theft system | Kensington lock |
| Certifications | FCC/CE |
| Touch screen support & Interactivity | Yes |
| Room Dock (peripheral support) | No |
| Local view | Yes |
| Network connection | LAN & WiFi |
| Management and reporting | Yes |
| Warranty | 1 year standard. 5 years coverage via SmartCare |
| * | * depends on configuration, available in future firmware updates |

Last updated: 25 May 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.