

## PSU-KP DSPK PSU KP-Series and DSPK panels KP Series



The PSU-KP is an in-line power supply used with KP-Series and DSPK4 Series keypanels. This is a universal power supply with 24 VDC output ability.

### Parts included

Quantity	Component
1	External Power Supply

### Technical specifications

#### Input Power

Connector type	IEC C14
Rated power (W)	60 W
Input voltage (VAC)	100 VAC – 240 VAC, +/- 10%, 50 - 60 Hz
Rated input current (A)	1.5 A

#### Output Power

Connector Type	Kycon #KPPX-3, 3-pin snap locking
Output voltage (VDC)	24 VDC, +/-5%
Output current (A)	2.5 A
Power Supply Efficiency Level	VI

- ▶ Universal power supply with 100 - 240 VAC input
- ▶ Standard IEC-320-C14 input connector
- ▶ Low earth leakage current

### Mechanical

Dimensions (H x W x D) (in)	1.3 in x 2.1 in x 4.6 in
Dimensions (H x W x D) (mm)	34.2 mm x 53.5 mm x 117.5 mm
Cable length (ft)	4 ft
Cable length (m)	1.2 m

### Environment

Operating temperature (°F)	-4 °F – 122 °F
Operating temperature (°C)	-20 °C – 50 °C, derated to 80% load
Operating relative humidity, non-condensing (%)	0% – 95%
Storage temperature (°F)	-22 °F – 176 °F
Storage temperature (°C)	-30 °C – 80 °C

### Ordering information

**PSU-KP DSPK PSU KP-Series and DSPK panels**  
 KP-Series and DSPK4 external power supply  
 Order number **PSU-KP DSPK | F.01U.410.185**