



UPS-3000-OL

TECHNICAL DESCRIPTION

The UPS-3000-OL shall be a two-rack-space or tower on-line UPS unit in a steel and plastic enclosure. It shall operate at 120 volts AC at both 50 or 60Hz and have a 6-foot, grounded, 3-wire #10 line cord. There shall be 5 grounded AC receptacles on the back panel. This unit can accommodate additional battery cabinets to extend its autonomous run time. Overall dimensions shall be 3.39" H x 17.24" W (or 19.0" W with ears) x 26.95" D. Weight shall be 81 pounds. The UPS-3000-OL shall have a total load rating of 3,000VA / 2,700 Watts. This unit can accommodate an optional SNMP network card for unit monitoring and shutdown.

SPECIFICATIONS	UPS-3000-OL
Load Rating	25A
Voltage Rating	120V
Power Requirement (no load)	0
Input/Mains Plug Type	L5-30P
Input/Mains Cord Length	5'6"
# of Receptacles	5
Receptacle Type	(1) L5-30R (4) 5-15/20R
Under-Voltage Auto Shutdown	Yes
Over-Voltage Auto Shutdown	Yes
Over-Current Auto Shutdown	Circuit Breaker
Over-Temperature Auto Shutdown	Internal temperature fault shutdown
Network Port	Optional SNMP Card
Serial Port	RS-232 on Female 9-pin D-subminiature USB Type B RJ45 on optional SNMP card
Temperature Sensor Input	None
BTU/h Max	1756 BTU/h
Auxiliary Relay Outputs	With optional relay card
Contact Closure Input	EPO and optional relay card
Dimensions	17.24" W x 26.95" D x 3.39" H
Weight	81 lbs
Temperature Range:	0C to 40C
Humidity Range	< 90% Non-condensing
Agency Listings	UL 1778 CSA-C22.2 No. 107.1

* 1.2 x 50 microsecond industry standard combination wave surge as per IEEE C62.41

** Specifications subject to change without notice

Specifications Version: ESP-SRX_Product_Specs_Master 03.20.20.xlsx

