



Sinergy III Series Battery Cabinet 3000 VA High / Low Voltage

Model Part Number	E072-12 17888-05R		
Туре	Sinergy III		
Compatible UPS	ACDEF3000-11 / ACDEF3000-22		
Voltage (Nominal)	72.0 VDC		
Battery Type	12V Flame Retardant Sealed Lead-Acid		
Battery Quantity	6 x 2 Strings		
Recharge Time	24 Hours (Single Battery Cabinet, 1A Charger)		
Length	17.25 in / 438 mm		
Height	3.39 in / 86 mm		
Depth	24.92 in / 633 mm		
Unit Weight	91.5 lbs. / 41.6 kg.		
Shipping Weight	105.0 lbs. / 47.4 kg.		
Safety Agencies	UL1778 cUL to CSA22.2 No. 107.1		

Percent		Number of Battery Cabinets					
Capacity Watts	Watts	Internal	INT+1 EXT	INT+2 EXT	INT+3 EXT	INT+4 EXT	
Runtimes are expressed in minutes Typical runtimes based on fully charged, new batteries, operating under typical load conditions Times estimated assuming a switch mode power supply Runtimes are affected by battery age, ambient temperature, site specific usage patterns and load con- ditions							
0	0	351	> 16 hrs	> 16 hrs	> 16 hrs	> 16 hrs	
10	240	56	247	491	772	> 16 hrs	
20	480	26	117	232	365	512	
30	720	16	72	144	226	318	
40	960	11	51	101	159	223	
50	1200	8.8	38	77	120	169	
60	1440	7.0	31	61	96	134	
70	1680	5.7	25	50	78	110	
80	1920	4.8	21	42	66	93	
90	2160	4.1	18	36	57	80	
100	2400	3.6	16	31	49	69	

Warranty/Support: Sinergy III Series products (hereafter referred to as "Product") are warranted to be free from defects in material and workmanship for two (2) years from date of shipment from POWERVAR, on the chassis & electronic components and two (2) years from date of shipment from POWERVAR on the batteries. This warranty is limited to repairing, replacing, or refurbishing, at POWERVAR's option, any defective component, circuit board or module within the Product. This warranty will include, at POWERVAR's sole discretion, on-site service or POWERVAR depot service. See the Limitations of Warranty section below for additional limitations & exclusions.

Battery Life Disclaimer: POWERVAR's standard battery warranty applies only to UPS and UPM products which are continuously connected to AC mains power, except during utility power outages. Products which are regularly and intentionally disconnected from AC mains power will experience battery discharge/charge cycles potentially far more numerous than those for which the battery was designed. As a result, products used in such applications will experience substantially reduced battery life. For that reason, POWERVAR's standard battery warranty does not apply for applications in which the UPS or UPM product is regularly and intentionally disconnected from AC mains power. POWERVAR UPS and UPM products used in such applications shall receive a 90 day warranty on batteries.

POWERVAR, Inc. - 1450 Lakeside Drive, Waukegan, IL 60085 POWERVAR, Ltd. - Unit 5 Birch, Kembrey Park, Swindon, Wiltshire, UK SN2 8UU