

# DCNM-FSLP Flush language selection panel

## DICENTIS



With the elegantly designed DICENTIS Flush language selection panel, participants can conveniently listen to the speaker in their preferred language directly to their headphones. Language selection is straightforward: it is automatically activated when the headphones are connected to the device. The participant can scroll through the available languages by pressing the illuminated touch buttons. If a preferred language for the participant is defined in the system, the language selector automatically uses the defined language.

Available languages can be displayed in native characters or as ISO abbreviations. The volume can also be adjusted through the illuminated touch buttons.

The DCNM-FSLP connects through an RJ12 connector to transfer data and to the DCNM-FBD2 headset connector for the audio.

### Functions

#### Display

- Language selection in original characters.
- Language selection in ISO abbreviation form.
- Language numbers.
- The display is off when the headphones are not connected.
- The display switches off automatically after not using any buttons for approximately 8 seconds, to minimize distractions from the meeting.

#### Headphones

- The panel allows you to control the headphones' volume so the interpretations or floor can be heard clearly even when there is excessive background noise.

- ▶ Supports up to 100 languages
- ▶ Indication of the native character language
- ▶ Automatic language selection
- ▶ Screen turns off to save energy and avoid distraction

- To prevent acoustical feedback, the volume control is automatically reduced when the participant is speaking.

#### Controls and indicators

- 1.44-inch display with 4 touch buttons.
- The LED indicators on the device show:
  - Left side: Headphone volume control.
  - Right side: Language selector.

#### Interconnections

- Control interface, through RJ12, to the DCNM-FBD2 and other devices.
- Connects to a DCNM-FBD2 through a CAN connection and through the headphone connection for the audio.
  - The DCNM-FBD2 supports one DCNM-FSLP per side.
- One 3.5 mm (0.14 in) headphone sockets stereo jack type.
- Connector for external headphones through soldering or through a connector.

#### Parts included

Quantity	Component
1	DCNM-FSLP Flush language selection panel
1	30 cm cable
1	Headphone connection cable

### Technical specifications

#### Audio

Frequency response (Hz)	100 Hz – 20000 Hz
Total harmonic distortion + noise (%)	0.10%
Dynamic range (dB)	90 dB
Minimum signal-to-noise ratio (dB)	90 dB

#### Headphones

Nominal output level (dBV)	0 dBV
Maximum output level (dBV)	3 dBV
Minimum impedance (Ω)	32 Ω
Maximum output power (mW)	65 mW

#### Electrical

Power consumption (W)	0.5 W
Operating voltage (VDC)	5 VDC

#### User interface

Display type	LCD
Display size (in)	1.44 in

#### Mechanical

Mounting type	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with the DCN-FCOUP Flush coupling and the DCNM-FEC Flush end cap in any surrounding
Dimensions (H x W x D) (mm)	56 mm x 100 mm x 51 mm
Dimensions (H x W x D) (in)	2.20 in x 3.94 in x 2.01 in
Weight (g)	67 g
Weight (lb)	0.15 lb
Color in RAL	RAL 9017 Traffic black

### Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Operating temperature (°C)	5 °C – 45 °C
Operating temperature (°F)	41 °F – 113 °F
Transportation temperature (°C)	-30 °C – 70 °C
Transportation temperature (°F)	-22 °F – 158 °F
Storage temperature (°C)	-5 °C – 45 °C
Storage temperature (°F)	23 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 90%

### Ordering information

**DCNM-FSLP Flush language selection panel**  
 Flush-mounted language selection panel.  
 Order number **DCNM-FSLP | F.01U.402.927**

### Software Options

**DCNM-LSSL License for language selector at 1 seat**  
 The DICENTIS Select Language at Seat license enables the language selection feature of the DICENTIS Multimedia and DICENTIS Discussion device with touchscreen. The DICENTIS Discussion device with language selector has the functionality built-in.  
 Order number **DCNM-LSSL | F.01U.300.534**

### Services

**EWE-DCNMFU-IW 12 mths wrty ext dicentis flush unit**  
 12 months warranty extension  
 Order number **EWE-DCNMFU-IW | F.01U.407.055**

#### Represented by:

**Europe, Middle East, Africa:**  
 Bosch Security Systems B.V.  
 P.O. Box 80002  
 5600 JB Eindhoven, The Netherlands  
 Phone: + 31 40 2577 284  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Germany:**  
 Bosch Sicherheitssysteme GmbH  
 Robert-Bosch-Ring 5  
 85630 Grasbrunn  
 Tel.: +49 (0)89 6290 0  
 Fax: +49 (0)89 6290 1020  
[de.securitysystems@bosch.com](mailto:de.securitysystems@bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**North America:**  
 Bosch Security Systems, LLC  
 130 Perinton Parkway  
 Fairport, New York, 14450, USA  
 Phone: +1 800 289 0096  
 Fax: +1 585 223 9180  
[onlinehelp@us.bosch.com](mailto:onlinehelp@us.bosch.com)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Asia-Pacific:**  
 Robert Bosch (SEA) Pte Ltd, Security Systems  
 11 Bishan Street 21  
 Singapore 573943  
 Phone: +65 6571 2808  
 Fax: +65 6571 2699  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)