



kramer

KAC-CAM-50L / KAC-CAM-50M

Video Camera



Choose the KAC-CAM-50L for large meeting rooms where a narrow field of view is essential or opt for the KAC-CAM-50M for smaller to medium rooms requiring a wider view. Both cameras are key components of the Kramer/ AudioCodes meeting rooms solutions, a bespoke collection of audio and video devices designed to create a fully integrated meeting room solution.

Compatibility is key, and these models excel with leading unified communications platforms such as Microsoft Teams and Zoom Rooms. Their ease of installation, thanks to a simple USB connection, and user-friendly operation, make them a top choice for enhancing your virtual meeting experience. Elevate your meetings with these state-of-the-art cameras, designed for simplicity, efficiency, and superior quality

FEATURES

- Crystal-clear image resolution at 4K/30fps resolution
- Intelligent zoom and facial recognition
- Seamless integration with Microsoft Teams, Zoom, and various UC platforms
- User-friendly setup and usage
- Powerful 10x digital zoom to easily focus on distant participants and objects
- Sleek, lightweight design with convenient mounting options for quick and effortless setup



kramer

TECHNICAL SPECIFICATIONS

Camera	<p>Image Sensor 1/2.5 inch high quality 4K CMOS sensor</p> <p>Effective Pixels 8.28MP, 16:9</p> <p>Video Output USB3.0, Type B. Support for audio signal output</p> <p>Video Resolution Main stream: 3840×2160 @30fps, 1920×1080P @30fps/25fps, 1280×720P@ 30fps/25fps Sub stream: 1280×720P @30fps/25fps, 640×480P @30fps/25fps, 320×172P @30fps/25fps</p> <p>Angle of View RXVCam50L 91° (D) / 81°(H) / 54°(V) RXVCam50M 102°(D) / 100°(H) / 64°(V)</p> <p>Focal Length RXVCam50L f=3.24mm, RXVCam50M f=2.26mm</p> <p>Aperture RXVCam50L F2.1, RXVCam50M F1.8</p> <p>Minimum Illumination 0.1Lux (F1.8, AGC ON)</p> <p>Digital Zoom 10x</p> <p>DNR 2D & 3D DNR</p>
USB	<p>Operating System Windows 7 (1080P/720P), Windows 8.1, Windows 10, macOS™ 10.10 and above, Linux (UVC)</p> <p>Video Compression YUY2, MJPG, H.264, H.265</p> <p>USB Protocol UVC, UAC</p> <p>PTZ Control Supports ePTZ</p> <p>Hardware Request 2.4 GHz Intel Core 2 Duo processor or better, 2GB capacity or more, USB 2.0, input (USB3.0 for 4K)</p>
Power	<p>Input Voltage DC 5V</p> <p>Input Current 1A (Max)</p> <p>Power Consumption 5W (Max)</p>
Environmental Conditions	<p>Store Temperature -10°C~+60°C</p> <p>Store Humidity 20%~90%</p> <p>Working Temperature -10C°~+50°C</p> <p>Working Humidity 20%~80%</p>
General	<p>Dimensions 220mm x 93.75mm x 56.5mm</p> <p>Application Indoor</p> <p>Accessories User manual, USB3.0 cable, remote controller</p>