



**C2G**  
**2x4 USB-C Switch With 2 USB-C Inputs To 2 USB-C And 2 USB-A Device Ports - USB 3.2 GEN 1 (5GBPS)**  
Part No. AVD\_CG\_C2G54263



For switching between two USB-C sources and two USB-C or USB-A devices, this device supports automatic switching by detecting a new source or manual switching via the front panel button or RS-232 API commands. It supports USB 3.2 Gen 1 with data transfer rates up to 5 Gbps and is compatible with a wide range of USB peripherals, including webcams, PTZ cameras, keyboards, mice, printers, displays, and more. This plug-and-play device is versatile and easy to use

## Features & Benefits

Two USB-C ports for host PC connection

Supports USB 3.2 Gen 1 with data transfer speeds up to 5Gbps

Compatible with a broad range of USB sources and devices

This USB switch is a plug-and-play device, ensuring easy and hassle-free setup without the need for additional drivers or software.

Two USB-C ports and two USB-A ports for connecting devices

Supports auto-switching when new devices are detected or manual switching via the front panel button or RS-232 API commands

Compatible with a variety of devices including webcams, PTZ cameras, keyboards, mice, printers, and displays.

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120542636	Country Of Origin	China
Features	RS232	Application Sector	Commercial, Residential
Warranty Type	3-Year	Type	Switch

### Dimensions

Product Width US	4.92 in	Product Weight US	1.1 lb
Product Depth US	3.15 in	Product Height US	1.18 in

### Listing Agencies / 3rd Party Agencies

CE Certified	Yes	FCC Compliant	Yes
REACH Compliant	Yes		

### Additional Information

---

RoHS Compliant	Yes
----------------	-----

---

### Technical Information

---

Data Transfer Rate	5 Gbps	Connector 2	USB-A Female, USB-A Female, USB-C Female, USB-C Female
Connector 1	USB-C Female, USB-C Female	Operating Temperature	32°-104°F (0°-40°C)

---