

MatrixPRO-II 16x16 DVI router

Affordable DVI router with HDCP support



- **Fast switching**
- **Programmable EDID support**
- **Integrated test pattern generator**

The MatrixPRO-II 16x16 DVI router is an HDCP compliant video signal matrix router that can switch any of the 16 DVI inputs to any or all of the 16 outputs. Any input source, whether it's an HD-DVD player, Blu-ray player or a computer with high-resolution graphics, can be routed to a DVI or HDMI (via an adaptor) output digital display.

Monitoring output

The MatrixPRO-II 16x16 DVI router accepts inputs up to 2,048 x 1,080 (including 1,920 x 1,200) resolutions. Each input is re-clocked as it passes through the router maintaining the DVI signal strength. Each channel can be programmed with unique EDID information based on the system requirements. In addition to the 16 outputs, the router includes a monitoring output to which any input can be routed to and allows users to monitor and verify the input signal before it is switched to the output.

With integrated test pattern generator

An integrated test pattern generator allows users to diagnose and solve any installation issues that may arise. The test pattern is available with or without any valid input signals. An optional redundant power supply is also available, enhancing the unit's reliability. The additional supply shares the load during the unit's operation, extending the lifetime of your power supplies.

Compatible with the other Barco image processing products

The MatrixPRO-II DVI-16x16 routers can be controlled in various ways:

- MatrixPRO-II 16x16 DVI front panel
- Encore and ScreenPRO-II controllers via Ethernet allowing for easy integration into the
- Barco Encore family of products

- Integrated web page server
- GUI program running on a windows PC

Features

- Fast switching
- Control from Encore & ScreenPRO-II controllers
- Signal re-clocking
- HDCP 1.0 support
- Programmable EDID support
- Monitor output
- All progressive resolutions from 480p up to WUXGA/HD
- Built-in test pattern
- LED indicators for valid input video and output device sense (HPD)

Mechanical

- Auto ranging power supply
- Optional redundant power supply
- Slim 4RU height
- Width: 19" rack

Product specifications**MATRIXPRO-II 16X16 DVI ROUTER****General specifications**

Control	<ul style="list-style-type: none">■ Ethernet RJ-45, 10/100 Mbps autosense■ Computer, tablet, smartphone, or Encore or ScreenPRO-II controller via Ethernet link■ Command line control via Telnet or RS-232 serial
Dimensions	440 x 380 x 178 mm (17 x 15 x 7 in) -4 RU rack mount
Weight	11 kg (24.2 lb)
DVI inputs and outputs	<ul style="list-style-type: none">■ Digital formats: All single-link DVI digital formats up to 165 Mhz, per DVI 1.0 specification■ EDID version 1.3 compatible■ HDCP version 1.0 compatible
Input power	100-240 VAC, 47-63 Hz, auto-selecting 2.0A maximum
Environmental	Humidity: 0-95% non-condensing
Temperature	0-40° C
Warranty	Full three-year parts and labor warranty

Last updated: 09 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.