

# Product datasheet

Specifications



## APC Back-UPS Pro, 1500VA/865W, Tower, 230V, 10x IEC C13 outlets, AVR, LCD, User Replaceable Battery

BR1500GI

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	230 V
Rated power in W	865 W
Rated power in VA	1500 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C13
Output connection type	5 IEC 60320 C13 5 IEC 60320 C13 surge 2 IEC Jumpers
Number of cables	1
Battery type	Lead-acid battery

### Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Number of battery replacement quantity	1
Battery voltage	24 V
Battery capacity	9.0 Ah
Battery charger power	23 W rated
Battery power in VAh	216 VAh capacity 187 VAh runtime
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC124</a>
Battery option	BR24BP 1 518 VAh BR24BPG 1 518 VAh
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0

## General

Provided equipment	1, detachable IEC power cord telephone cable user manual USB cable
--------------------	---

Number of power module free slots	0
-----------------------------------	---

Number of power module filled slots	0
-------------------------------------	---

Redundant	No
-----------	----

## Physical

Colour	Black
--------	-------

Height	30.1 cm
--------	---------

Width	11.2 cm
-------	---------

Depth	38 cm
-------	-------

Net weight	12.7 kg
------------	---------

Mounting preference	No preference
---------------------	---------------

Mounting mode	Not rack-mountable
---------------	--------------------

Two post mountable	0
--------------------	---

USB compatible	No
----------------	----

## Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
-------------------	--------------------------------

Input voltage limits	156...300 V adjustable 176...294 V
----------------------	---------------------------------------

Switching current capacity	10 A
----------------------------	------

## Output

Maximum configurable power in W	865 W
---------------------------------	-------

Output frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

Crest factor	3 : 1
--------------	-------

UPS type	Line interactive
----------	------------------

Wave type	Stepped approximation to a sinewave
-----------	-------------------------------------

Maximum configurable power in VA	1500 VA
----------------------------------	---------

Transfer time	10 ms typical : 12 ms maximum
---------------	-------------------------------

## Conformance

Product certifications	A-Tick C-Tick CE GOST Telepermit TÜV
------------------------	---

Marking	GS Mark
---------	---------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

Equipment protection policy	Lifetime : 200000 AUD Lifetime : 150000 euros
-----------------------------	--

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...30000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	45 dBA

## Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rate	441 J
Noise suppression	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	38.7 cm
Package 1 Width	23.8 cm
Package 1 Length	48.8 cm
Package 1 Weight	14.3 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	24
Package 2 Height	132 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	342.48 kg
SCC14	10731304268748

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

---

Warranty

2 years repair or replace, 3 years repair or replace for European Union countries

Recommended replacement(s)