



# kramer

## TP-582T

2x1 HDMI switchable Transmitter with Ethernet, RS-232 & IR over Extended-Reach HDBaseT

| HDMI | Ethernet - RJ-45 | HDCP Compliant  
| HDBaseT



TP-582T is a high-performance, extended-reach HDBaseT switchable transmitter for 1080p60Hz HDMI, Ethernet, RS-232 and IR signals over twisted pair. The TP-582T converts all input signals into the transmitted HDBaseT signal. It extends video signals to up to 130m (430ft) over CAT copper cables at up to 1080p@60Hz 36bpp video resolution. The TP-582R converts the HDBaseT twisted pair signal back to Ethernet, RS-232, IR and two HDMI outputs, and de-embeds the audio to S/PDIF and TOSLINK® audio outputs

## FEATURES

**High Performance Standard Extender** - Switchable, professional HDBaseT extender for providing extended-reach signals over twisted-pair copper infrastructures. TP-582T is a standard extender that can be connected to any market-available HDBaseT-compliant extension product. For optimum extension reach and performance, use recommended Kramer cables

**HDMI Signal Extension** - HDCP 2.2 compliant. Supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, and 3D. EDID signals are passed through from the source to the display

**I-EDIDPro™ Kramer Intelligent EDID Processing™** - Intelligent EDID handling, processing and pass-through algorithm that ensures Plug and Play operation for HDMI source and display systems

**Multi-channel Audio Extension** - Up to 8 channels of digital stereo uncompressed signals for supporting studio-grade surround sound

**Ethernet Extension** - Ethernet interface data flows in both directions, allowing extension of up to 100Mbps Ethernet connectivity for LAN communication and device control

**Bidirectional RS-232 Extension** - Serial interface data flows in both directions, allowing data transmission and device control

**Bidirectional Infrared Extension** - IR interface data flows in both directions, allowing remote control of peripheral devices located at either end of the extended line

**Simple Control Operation** - Easy selection of input video signals for its extension, locally via front panel button, or remotely via either remote IR control or control buttons connected to rear panel contact closures

**Cost-effective Maintenance** - Status LED indicators for HDMI and HDBT ports facilitate easy local maintenance and troubleshooting

**Easy and Elegant Installation** - Compact MegaTOOLS™ fan-less enclosure for dropped-ceiling mounting, or side-by-side mounting of 2 units in a 1U rack space with the recommended rack adapter



# kramer

## TECHNICAL SPECIFICATIONS

---

INPUTS:	2 HDMI on HDMI connectors, 1 remote IR sensor, 2 remote contact closures on a 3-pin terminal block connector
OUTPUT:	1 HDBT on an RJ-45 female connector
PORTS:	1 IR on a 3.5mm mini jack for IR link extension, 1 RS-232 on a 9-pin D-sub connector for serial link extension, 1 10Base-T/100BaseTx Ethernet on an RJ-45 female connector for LAN extension
EXTENSION LINE:	HDBaseT 1.0 compliant; up to 130m (430ft) at full HD (1080p @60Hz 36bpp); Note: When using Kramer HDBaseT cables
VIDEO:	Up to 6.75Gbps bandwidth (2.25Gbps per graphic channel), Up to 1080p@60Hz 36bpp resolution, HDCP 2.2 signal compliance
EXTENDED ETHERNET:	Up to 100Mbps extended line rate bandwidth
EXTENDED RS-232:	300 to 115200 baud rate
POWER SOURCE:	5V DC, 4A
POWER CONSUMPTION:	5V DC, 800mA
ENCLOSURE:	Mega Tools size, aluminum type
COOLING:	Convection ventilation
INCLUDED ACCESSORIES:	Power supply 5V/4A, bracket installation kit
Product Dimensions	19.00cm x 11.50cm x 2.70cm (7.48" x 4.53" x 1.06" ) W, D, H
Product Weight	0.4kg (1.0lbs) approx
Shipping Dimensions	34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05" ) W, D, H
Shipping Weight	1.0kg (2.1lbs) approx



