

Product data sheet

Specifications



Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 5.7kW, 208V, (21) C13 & (3) C19

AP8661

Overview

Presentation

APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering. Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.

Lead time Usually in Stock

Main

Main Input Voltage 208 V 3 phase

PDU Type Switched metered outlet

Main Output Voltage 208 V

Input Connection Type NEMA L21-20P

Number of rack unit 0U

Cable length 6 ft (1.83 m)

Number of cables 1

Provided Equipment CAN Port Terminator
Installation guide
Rack Mounting brackets
Safety guide
Serial configuration cable

Physical

Color Black

Height 72.01 in (182.9 cm)

Width 2.20 in (5.6 cm)

Depth 2.01 in (5.1 cm)

Net Weight 15.74 lb(US) (7.14 kg)

Mounting Location Side

Mounting preference No preference

Mounting Mode Rack-mounted

USB compatible No

Mounting position	Vertical
-------------------	----------

Input

Line Rated Current	16 A
Max line current	20 A
Input current limits	20 A
Load Capacity	5700 VA
Input Frequency	50/60 Hz

Output

Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Product Certifications	cUL Listed UL Listed VCCI Class A
Standards	FCC Part 15 class A ICES-003

Environmental

Ambient air temperature for operation	23...140 °F (-5...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

GTIN	731304276999
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	80.24 in (203.8 cm)
Package 1 Width	4.65 in (11.8 cm)
Package 1 Length	6.38 in (16.2 cm)
Package 1 Weight	20.75 lb(US) (9.41 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Recommended replacement(s)