



# kramer

## KDS-DEC7

High-performance, highly-scalable, AVoIP  
Decoder for 4K60 4:2:0, HDR10 over 1G  
network

| HDMI | Ethernet - RJ-45 | 4K/60 UHD (4:2:0)  
| HDCP 2.2 Compatible



KDS-DEC7 decoder is an advanced receiver for streaming 4K@30Hz (4:4:4) video signals via Ethernet over copper cable. It decodes streams over an IP network to HDMI output, and transmit the USB, IR, RS-232, or CEC signal over IP network

## FEATURES

### Outstanding end-user experience -

Rich set of inputs and interfaces

Easy-to-use KM/KVM - Searchable OSD Menu for KM and fully configurable KVM roaming

Large scale video wall - up to 16x16

Instantaneous switching time - 1 second

### Ideal for large-scale deployments -

Highly scalable - 999 channels build in support

State of the art management device

Rich set of management capabilities - Standard P3K Open API , LCD screen for configuration

### Robust security -

Enterprise IT-grade security - 802.1x and HTTPS/TLS

Security certification - OWASP Top 10 certificate

Separate ETH ports for optimal security and experience

New HW architecture that enables robust FW update

### Simple planning and rollout: -

Cost-effective from day one

Full product range for any site, any application

Plug-and-play with Netgear M4250 AVoIP switches, Kramer Control, KDS-USB2, etc.

### PoE Support -

Using PoE switch - up to 13W consumption

### Alternative sources/destinations -

HDMI Loop-Through on Encoder and HDMI Input on Decoder

### Analog Audio -

Embedding and De-embedding

### Control gateway -

Through P3K control/communicate with IR, RS232, or CEC to the connected devices



# kramer

## TECHNICAL SPECIFICATIONS

---

Inputs	1 HDMI: On a female HDMI connector
Outputs	1 HDMI: On a female HDMI connector
Ports	2 Ethernets: On R-J45 connectors 1 Balanced Audio: On a 5-pin terminal block connector 1 RS-232: On a 3-pin terminal block connector 1 IR: On a 3.5mm TRS connector 2 USB: On USB-A connectors
Video	Compression Standard: JPEG based, private stream Max Resolution: 4K@30Hz 4:4:4 HDR 10: Up to 4K30 4:2:2 12 bit
Video Streaming	Compression Standard: JPEG2K based, proprietary stream Max Input Resolution: 4K@60hz (4:2:0) Max Output Resolution: 4K@30hz (4:4:4) Max End-to-End Resolution: 4K@30hz (4:4:4) + HDR 10bit Scaler: Yes End-to-End Latency: 33msec Switching Time: 1sec
Audio	Supported Formats: LPCM upto 7.1/24-bit/192kHz, Dolby Atmos™, Dolby TrueHD, Dolby Digital Plus™, Dolby Digital EX, Dolby Digital 5.1, Dolby Digital 2/0 Surround, Dolby Digital 2/0, DTS-HD Master Audio™, DTS-HD, DTS-ES Discrete 6.1, DTS-ES Matrix 6.1, DTS Digital Surround 5.1
User Interface	Indicators: LINK, NET and ON LEDs, front panel LCD Display Controls: Restart and factory reset rear panel button, embedded web pages, P3K API commands via Ethernet, front panel navigation buttons
Power	PoE (Power over Ethernet) 37V to 57V, max power 13W Optional power supply 24V DC, 5A
Environmental Conditions	Operating Temperature: 0 to + 45°C (32 to + 113 °F), 10% to 90%, non-condensing Storage Temperature: -20 to +70°C (-4 to + 158 °F), 10% to 90%, non-condensing Humidity: 10% to 90%, non-condensing
Product Dimensions	18.90cm x 14.50cm x 2.76cm (7.44" x 5.71" x 1.09" ) W, D, H
Product Weight	0.7kg (1.5lbs) approx
Shipping Dimensions	31.20cm x 17.90cm x 7.60cm (12.28" x 7.05" x 2.99" ) W, D, H
Shipping Weight	0.9kg (2.1lbs) approx

